Listing of Claims:

5

10

15

20

1. (Currently Amended) A time-data transmitting apparatus comprising:

a time-measuring portion which measures current time data;

a radio-wave reception control portion which receives a

standard-time radio wave signal containing time data;

a time-correcting portion which corrects the current time data measured by the time-measuring portion based on the time data contained in the standard-time radio wave signal received by the radio-wave reception control portion;

a transmission-demand signal receiving reception control portion which receives a weak-wave transmission-demand signal; and

a transmission control portion which transmits a radio wave containing time data <u>based on the current time data measured by the time-measuring portion</u>, at a predetermined time <u>and</u> at a first intensity, <u>and which, for a predetermined time period</u>, <u>halts transmission of the and a radio wave containing the time data [[,]] at the first intensity and performs transmission thereof at a second intensity <u>that is</u> lower than the first intensity, when the transmission-demand signal <u>receiving reception control</u> portion receives the weak-wave transmission-demand signal.</u>

Claims 2 and 3 (Canceled).

- (Currently Amended) The time-data transmitting apparatus according to claim 1, wherein the weak-wave transmission-demand signal is a signal transmitted from a wristwatch.
- (Original) The time-data transmitting apparatus according to claim 1, wherein the time data contained in the radio wave represents time in minimum units of minutes.
- (Currently Amended) The time-data transmitting apparatus according to claim 1, wherein the predetermined time is has a one-minute interval.
- 7. (Currently Amended) The time-data transmitting apparatus according to claim ϑ 1, wherein the radio wave transmitted from the transmission control portion is of the <u>a</u> same frequency and same format as the standard-time radio wave signal.
- 8. (Currently Amended) The time-data transmitting apparatus according to claim θ 1, wherein at least one of a frequency and a format of the radio wave transmitted from the transmission

5

5

10

5

control portion is of a frequency and format, at least one of which differs from that of the standard-time radio wave signal.

9. (Currently Amended) A time-data transmitting apparatus comprising:

an external operation switch; and

a transmission control portion which transmits a radio wave containing time data, at a predetermined time <u>and</u> at a first intensity, <u>and which, for a predetermined time period, halts transmission of the and a radio wave containing the time data [[,]] at the first intensity and performs transmission thereof at a second intensity <u>that is</u> lower than the first intensity, when the external operation switch is operated.</u>

Claim 10 (Canceled).

- 11. (Currently Amended) The time-data transmitting apparatus according to claim 9, further having comprising:
- a time-measuring portion which measures $\frac{1}{1}$ current time data:
- a standard radio-wave receiving portion which receives a standard-time radio wave signal containing time data; and
- a time-correcting portion which corrects the current time data measured by the time-measuring portion, on the basis of

10

5

<u>based on</u> the time data contained in the standard-time radio wave signal received by the standard radio-wave receiving portion,

wherein the transmission control portion transmits $\underline{\text{the}}$ radio wave that contains the time data based on the current time data measured by the time-measuring portion.

- 12. (Original) The time-data transmitting apparatus according to claim 9, wherein the time data contained in the radio wave represents time in minimum units of minutes.
- 13. (Currently Amended) The time-data transmitting apparatus according to claim 9, wherein the predetermined time is has a one-minute interval.
- 14. (Currently Amended) The time-data transmitting apparatus according to claim 11, wherein the radio wave transmitted from the transmission control portion is of the a same frequency and same format as the standard-time radio wave signal.
- 15. (Currently Amended) The time-data transmitting apparatus according to claim 11, wherein at least one of a frequency and a format of the radio wave transmitted from the transmission control portion is of a frequency and format, at

5

10

15

2.0

- 5 least one of which differs from that of the standard-time radio wave signal.
 - 16. (Currently Amended) A time-correcting system comprising:
 - (i) a time-data transmitting apparatus which comprises: a time-measuring portion which measures current time data;
 - a radio-wave reception control portion which receives a standard-time radio wave signal containing time data;
 - a time-correcting portion which corrects the current time data measured by the time-measuring portion based on the time data contained in the standard-time radio wave signal received by the radio-wave reception control portion;
 - a transmission-demand receiving signal reception control portion which receives a weak-wave transmission-demand signal; and
 - a transmission control portion which transmits a radio wave containing time data <u>based on the current time data measured</u> by the time measuring portion, at a predetermined time <u>and</u> at a first intensity, <u>and which, for a predetermined time period</u>, <u>halts transmission of the and a radio wave containing the time data [[,]] at the first intensity and performs transmission thereof</u> at a second intensity <u>that is</u> lower than the first

Application Serial No. 10/534,367 Response to Office Action

intensity, when the transmission-demand receiving signal reception control portion receives the weak-wave transmission-demand signal, and

(ii) a clock which comprises:

2.5

30

35

5

a time-measuring portion which measures $\frac{\mbox{\footnotesize the}}{\mbox{\footnotesize time;}}$

a transmission-demand transmitting portion which $\label{transmits} \text{transmits the weak-wave transmission-demand signal;}$

a wave-receiving portion which receives a radio wave that is transmitted from the time-data transmitting apparatus and containing that contains a time code; and

a time-correcting portion which corrects the time on the basis of based on the time data code received by the wave-receiving portion.

Claims 17 and 18 (Canceled).

19. (Currently Amended) The time-correcting system according to claim [[18]] 16, wherein the clock further has comprises a standard radio-wave receiving portion which receives the standard-time radio wave signal containing the time data, and

wherein the time-correcting portion for the clock further corrects the current time data measured by the time-measuring

Application Serial No. 10/534,367 Response to Office Action

10

portion, on the basis of <u>based on</u> the time data contained in the standard-time radio wave signal received by the standard radio-wave receiving portion.

20. (Original) The time-correcting system according to claim 16, wherein the clock comprises a band for strapping the clock on the arm of a user.